



### **Electric Strike ICS GK310LS**

Electric strike with operating voltage 12 or 24Vdc.

Selectable fail safe/fail secure. Operating temperature: -10°C – 45°C

Horizontal or vertical installation. Tested to 1.000.000 cycles.



[Press for data sheet](#)

### **Electric Strike ICS GK311-1224**

Electric strike with operating voltage 12 or 24Vdc.

Selectable fail safe/fail secure. Operating temperature: -10°C – 45°C

Horizontal or vertical installation. Tested to 1.000.000 cycles



[Press for data sheet](#)



### **Electric Strike Adams Rite 7100**

Electric strike with operating voltage 12 or 24Vdc.

Fail safe/fail secure convertible without any additional parts.

Standards: ANSI/BHMA 156.5 Grade 1. UL Listed for burglary resistance.



[Press for data sheet](#)



### **Electric Strike Nadal Badal 1410**

Electric strike with operating voltage 12Vdc. Fail Secure. Operating temperature -10°C + 60°C. Optional electrical protection.



[Press for data sheet](#)

### **Electric Strike Nadal Badal 1411**

Electric strike with operating voltage 12Vdc. Fail Safe. Operating temperature -10°C + 60°C. Optional electrical protection.



[Press for data sheet](#)



### **Electric Strike Nadal Badal 1580**

Electric strike fire resistance from 60°C to 1.200 °C with operating voltage 12Vdc or 24 Vdc. Fail Secure.

Operating temperature -10°C + 60°C. Optional electrical protection.



[Press for data sheet](#)