



Rack & Pinion Overhead Door Closers



DOOR CLOSER DORMA TS 68

Selectable closing force: EN2/3/4
Standard doors: ≤1100mm και weight 80kg Suitable for fire and smoke doors
Closing speed adjustable:
0°-15°, 15°-180°

Backcheck
Without delayed action
Dimensions: Length: 220mm x Width: 45mm x Height: 53.5mm
EN 1154

[Press for data sheet](#)



DOOR CLOSER DORMA TS 72

Spring Strength: EN2-4 Standard doors:
≤1100mm and weight 80kg
Suitable for fire and smoke doors Closing speed adjustable: 0°-15°, 15°-180°

Latching action adjustable
Delayed action
Hold open: Dimensions: Length: 232mm x Width: 45mm x Height: 67mm
EN 1154, CE-mark

[Press for data sheet](#)



DOOR CLOSER DORMA TS 83

Spring Strength: EN3-6, EN7 Standard and external doors:

EN3-6 - ≤1400mm, EN7 - ≤1600mm και weight 160 kg

Suitable for fire and smoke doors Closing speed adjustable: EN3-6: 0°-15°, 15°-180°, EN7: Various Adjustable latching action: by arm. Delayed action variable Hold open

Dimensions: Length: 245mm x Width: 46mm x Height: 60mm (EN3-6)

Dimensions: Length: 293mm x Width: 47.5mm x Height: 60mm (EN7)

EN 1154, CE-mark

[Press for data sheet](#)



DOOR CLOSER ECO TS 10

Adjustable Spring Power: EN2-4

Suitable for doors: EN2-4 - ≤1100mm

Suitable for fire and smoke doors

Adjustable closing speed

Adjustable delayed action

Without delayed action

Hold open

Dimensions: Length: 220mm x Height: 60mm (EN2-4) EN 1154

[Press for data sheet](#)



DOOR CLOSER ECO TS 14

Adjustable Spring Power: EN2-4

Suitable for doors: EN2-4 - ≤ 1100 mm

Suitable for fire and smoke doors

Adjustable closing speed

Adjustable delayed action

Without delayed action

Hold open

Dimensions: Length: 214mm x Width: 41mm x Height: 60mm (EN2-4) EN 1154, CE-mark

[Press for data sheet](#)