



## **FLOOR SPRINGS**



### **FLOOR SPRING DORMA BTS 75V**

Spring Strength: EN1-4, Standard and External Doors:  $\leq 1100$ mm Suitable for fire and smoke doors  
Max. leaf weight 120 Kg. Suitable for single and double action doors. Non handed Closing Speed: 0o-15o,  
15o-175o Hold-Open: 90o or 105o. Dimensions: Length: 285mm x Width: 82mm x Height: 50mm. EN 1154,  
CE-mark



### **FLOOR SPRING DORMA BTS 80**

Spring Strength: EN 3/4/6 Standard and External Doors:  $\leq 950/\leq 1100/\leq 1400$ mm Max. leaf weight  
300Kg. Suitable for single and double action doors. Suitable for fire and smoke doors. Non handed.  
Closing Speed: 0°-175° Delayed action adjustable by valve Hold-Open: 90° or 105° Dimensions: Length:  
341mm x Width: 78mm x Height: 60mm, EN 1154, CE-mark



### **FLOOR SPRING DORMA BTS 84**

Spring Strength: EN2, EN3, EN4 Standard and External Doors: Closing speed variable Hold-open point 90o, EN2: ≤850mm, EN3: ≤950mmEN4: ≤1100mm Max. leaf weight 100 Kg Suitable for single and double doors. Suitable for fire and smoke doors. Dimensions: Length: 306mm x Width: 108mm x Height: 40mm EN 1154, CE-mark (EN3, EN4)